

E6911 Domo spreadlight
Tapered brushed nickel
12v – IP56

Elipta Domo spreadlights provide a wide soft pool of light for the illumination of paths or steps and around the terrace, drive and lawn. The Domo 12v spreadlight hides the light source under the shade and gives off a low glare and a pool of light roughly 3m in diameter

**PHYSICAL DATA**

- Nickel plated copper tubular stem
- Die-cast brass body
- High grade spun copper shade, nickel plated and brush finished
- Heat resistant frosted glass dome
- Polycarbonate ground spike included

ELECTRICAL DATA

- 12v – requires power from a remote transformer
- Pre-wired with 1.5m two core 1.0mm² H07RN-F cable

COMPATIBLE LAMPS (purchase separately)

- G4 LED capsule lamps

INSTALLATION

- Join the pre-wired 1.5m cable to low voltage supply cable by crimped heat shrink joint - order cable joint kit T9962 separately
- Connect into a cable run supplying several fittings with a T9963 cable splice kit
- T9963 are ideal for connections with 4mm low voltage cable, especially on longer cable runs

PACKAGING

- Stem 495mm x 60mm x 60mm – 0.6Kg.
- Glass assembly 135mm x 100mm x 100mm – 0.45Kg
- Shade 245mm x 75mm – 0.5kg

COMPLIANCE & WARRANTY

- 2 year warranty
- CE / RoHS Compliant

