



01604 495 151
collingwoodlighting.com

 collingwoodled
 /collingwoodlighting
 collingwoodlighting

GL016RGBW

LED colour change ground light (5W max.)

Features

IK rating	IK09
IP rating	IP67
CSP Switchable	RGBW
Walk Over / Drive Over	Walk over
LED Lifetime	50,000h L50
SDCM	3 SDCM

Installation information

Cut Out Size	Ø 50mm
UK Bathroom Zone	1
Construction Material	Stainless steel (316)
Weight	300g
Maximum Ambient Temperature	35°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	W	Colour	Beam	lm	lm/W	lx @ 1m
GL016RGBW	1.2W	White (4000K)	40°	50	42	74
GL016RGBW	1.2W	Red	40°	38	38	75
GL016RGBW	1.2W	Green	40°	63	53	124
GL016RGBW	1.2W	Blue	40°	11	9	17

Wiring information

Cable / Flying Lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of Wiring Required	Series

LED drivers

PR3011	220-240V	-	Yes	1	1	6
N/A	N/A	-	Yes	1	N/A	N/A

Accessories

TUBE/50	Installation tube	Sold Separately
JB7	5-pole IP68 inline connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
RC2819 / WC2820(BLK/W H) / TR2818	4/6/8 zone RF control for RGB & RGBW system	Sold Separately

Guarantee

5 year extended warranty

Features & benefits

RGBW
 Coastal protected
 IK08 suitable for pathways
 Installation tube available
 Low profile for easy installation
 Separate white LED for permanent use
 Compatible with a large range of controllers
 Marine grade stainless steel for use in outdoor and indoor environments

Beam angle: 40°

