



GL018 C AB

0.5W, 31mm mini antique brass marker ground light

Features

IK rating	IK07
IP rating	IP68
CSP Switchable	Fixed colour
Walk Over / Drive Over	Walk over
LED Lifetime	30,000h L70
CRI	80 Ra
SDCM	3 SDCM

Installation information

Cut Out Size	Ø 28mm
UK Bathroom Zone	0
Construction Material	Brass
Weight	300g
Maximum Ambient Temperature	35°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	W	Colour	Beam	lm	lm/W	lx @ 1m
GL018 C AB NW	0.5W	4000K	120°	3	6	1
GL018 C AB WW	0.4W	3000K	120°	4	10	1
GL018 C AB 27	0.5W	2700K	120°	3	6	1
GL018 C AB BLUE	0.5W	Blue	120°	0.5	1.3	0.18

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Parallel

LED drivers

PSI524	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	30
PS5024	N/A	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	100
PSDIP10024	N/A	Yes	Yes (1-10V)	0 (1 when dimming)	1	200

Accessories

JB1 / JB5 / JB6	IP68 waterproof connectors
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
PDCINT1-10V	1-10V dimming interface for use with 24V LED drivers



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

3 year extended warranty (see "NEW" codes which now have a 7 year extended warranty)

Features & benefits

- 0.5W at 24V DC
- Frosted effect for low glare and soft lighting
- Low voltage groundlight
- Solid brass with antique effect
- Robust cable for outdoor use
- Shallow depth for easy installation
- Easy and quick installation with parallel wiring

Beam angle: 120°

