



GL018 C

0.5W, 31mm mini round marker ground light

Features

IK rating	IK07
IP rating	IP68
CSP Switchable	Fixed colour
Walk Over / Drive Over	Walk over
LED Lifetime	30,000h L70
CRI	80 Ra
SDCM	3 SDCM

Installation information

Cut Out Size	Ø 28mm
UK Bathroom Zone	0
Construction Material	Stainless steel (316)
Weight	300g
Maximum Ambient Temperature	35°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Feature I	W	Colour	Beam	lm	lm/W	lx @ 1m
GL018 C NW	NEW	0.4W	4000K	120°	4	10	1
GL018 C 27	NEW	0.4W	2700K	120°	4	10	1
GL018 C BLUE	NEW	0.4W	Blue	120°	0.5	1.3	0.18

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Parallel

LED drivers

PS1524	220-240V	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	30
PS5024	N/A	Yes	Yes (with PDCINT 1-10V)	0 (1 when dimming)	1	100
PSDIP10024	N/A	Yes	Yes (1-10V)	0 (1 when dimming)	1	200

Accessories

JB1 / JB5 / JB6	IP68 waterproof connectors
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
PDCINT1-10V	1-10V dimming interface for use with 24V LED drivers



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

3 year extended warranty (see "NEW" codes which now have a 7 year extended warranty)

Features & benefits

0.5W at 24V DC

Frosted effect for low glare and soft lighting

Low voltage groundlight

Robust cable for outdoor use

Shallow depth for easy installation

Coastal protected

Easy and quick installation with parallel wiring

Beam angle: 120°

