



GL019 SQ

Up to 2W, 130lm square mini ground light

Features

IK rating	IK07
IP rating	IP68
CSP Switchable	Fixed colour
Walk Over / Drive Over	Walk over
LED Lifetime	70,000h L70
CRI	80 Ra
SDCM	3 SDCM

Installation information

Cut Out Size	Ø 33mm
UK Bathroom Zone	0
Construction Material	Stainless steel (316)
Weight	134g
Maximum Ambient Temperature	50°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Colour	Beam	W	lm	lm/W	lx @ 1m	W	lm	lm/W	lx @ 1m
			350mA				700mA			
GL019 SQ F NW	4000K	20°	1W	90	35	396	2W	130	-	572
GL019 SQ S NW	4000K	12°	1W	90	90	1833	2W	130	65	2648
GL019 SQ F BLUE	Blue	20°	1W	10	90	44	2W	20	65	88
GL019 SQ S BLUE	Blue	12°	1W	10	10	204	2W	20	10	407

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

PLU/350 1-9	220-240V	Yes	No	1	1	9
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	10
PLU/700 3-9	N/A	Yes	No	1	3	9

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors
TUBE332	Installation tube
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

7 year extended warranty

Features & benefits

1W at 350mA or 2W at 700mA

Coastal protected

Low voltage groundlight

Square baffle for a different decorative effect

Shallow depth for easy installation

Marine-grade stainless steel 316

Light source energy efficiency:



Beam angles: 12° 20°

