




GL100

Up to 2W, 14lm mini domed marker light

Features

IK rating	IK07
IP rating	IP68
CSP Switchable	Fixed colour
Walk Over / Drive Over	Walk over
LED Lifetime	70,000h L70
CRI	80 Ra
SDCM	3 SDCM

Installation information

Cut Out Size	Ø 33mm
UK Bathroom Zone	0
Construction Material	Stainless steel (316) or brass
Weight	221g
Maximum Ambient Temperature	35°C
Electric Class (1, 2, 3)	3

Wiring information

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED drivers

PLR/350 1-5	220-240V	Yes	No	0	1	5
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (I-10V)	2	1	10
PLU/700 3-9	N/A	Yes	No	1	3	9

Accessories

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold Separately
TUBE332	Installation tube	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

7 year extended warranty



Features & benefits

- 1W at 350mA or 2W at 700mA
- Coastal protected
- Low voltage groundlight
- Walk over groundlight ideal for paths or steps
- Marine-grade Stainless Steel 316
- IP68 rated
- Long-lifetime of 70,000hrs
- 7-year warranty

Light source
energy efficiency:



Beam angles: C0/C180 C90/C270





collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

GL100

The GL100 creates a grazing light effect from a domed, marine-grade stainless steel 316 housing. This product is available in five different window styles and three colour temperatures to suit a wide range of applications. This is ideal for providing low-glare, decorative illumination of pathways, decking and steps.

Photometrics @ 25°C

Product code	Feature I	Feature II	Colour	Beam	W	lm	lm/W	W	lm	lm/W
					350mA			700mA		
GL100DX1X27	1 window	Stainless Steel 316	2700K	75°	1W	2	2	2W	3	2
GL100DX1X30	1 window	Stainless Steel 316	3000K	75°	1W	2	2	2W	4	2
GL100DX1X40	1 window	Stainless Steel 316	4000K	75°	1W	3	3	2W	4	2
GL100DX2127	2 windows, 1 direction	Stainless Steel 316	2700K	75°	1W	4	4	2W	6	3
GL100DX2130	2 windows, 1 direction	Stainless Steel 316	3000K	75°	1W	4	4	2W	8	4
GL100DX2140	2 windows, 1 direction	Stainless Steel 316	4000K	75°	1W	6	6	2W	7	4
GL100DX2227	2 windows, 2 directions	Stainless Steel 316	2700K	75°	1W	4	4	2W	6	3
GL100DX2230	2 windows, 2 directions	Stainless Steel 316	3000K	75°	1W	4	4	2W	8	4
GL100DX2240	2 windows, 2 directions	Stainless Steel 316	4000K	75°	1W	6	6	2W	7	4
GL100DX3X27	3 windows	Stainless Steel 316	2700K	75°	1W	6	6	2W	9	5
GL100DX3X30	3 windows	Stainless Steel 316	3000K	75°	1W	6	6	2W	12	6
GL100DX3X40	3 windows	Stainless Steel 316	4000K	75°	1W	9	9	2W	11	5
GL100DX4X27	4 windows	Stainless Steel 316	2700K	75°	1W	8	8	2W	12	6
GL100DX4X30	4 windows	Stainless Steel 316	3000K	75°	1W	8	8	2W	14	7
GL100DX4X40	4 windows	Stainless Steel 316	4000K	75°	1W	12	12	2W	14	7
GL100AX1X27	1 window	Antique Brass	2700K	75°	1W	2	2	2W	3	2
GL100AX1X30	1 window	Antique Brass	3000K	75°	1W	2	2	2W	4	2
GL100AX2127	2 windows, 1 direction	Antique Brass	2700K	75°	1W	4	4	2W	6	3
GL100AX2130	2 windows, 1 direction	Antique Brass	3000K	75°	1W	4	4	2W	8	4
GL100AX2227	2 windows, 2 directions	Antique Brass	2700K	75°	1W	4	4	2W	6	3
GL100AX2230	2 windows, 2 directions	Antique Brass	3000K	75°	1W	4	4	2W	8	4
GL100AX3X27	3 windows	Antique Brass	2700K	75°	1W	6	6	2W	9	5
GL100AX3X30	3 windows	Antique Brass	3000K	75°	1W	6	6	2W	12	6
GL100AX4X27	4 windows	Antique Brass	2700K	75°	1W	8	8	2W	12	6
GL100AX4X30	4 windows	Antique Brass	3000K	75°	1W	8	8	2W	14	7