



UL010

Universal LED light

Features

IP rating	IP68
Tilttable	360°
Rotation Angle	360°
Dimmable Option	Yes with suitable driver
LED Lifetime	70,000h L70
CRI	80 Ra
SDCM	3 SDCM

Installation information

Construction Material	Stainless steel (316)
Weight	500g
Maximum Ambient Temperature	35°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
UL010 NW	Stainless steel 316	3W	4000K	26°	119	40	648
UL010 WW	Stainless steel 316	3W	3000K	26°	95	32	411
UL010 27	Stainless steel 316	3W	2700K	26°	92	31	399
UL010 A WW	Brass	3W	3000K	26°	95	32	411
UL010 A 27	Brass	3W	2700K	26°	92	31	399
UL010 B 30	Black anodised aluminium	3W	3000K	26°	95	32	411
UL010 B 27	Black anodised aluminium	3W	2700K	26°	92	31	399

Wiring information

Cable / Flying Lead	3m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

Accessories

JB2 / JB4	Waterproof junction box / Gel filled waterproof connector	Sold Separately
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold Separately
WCR 275 BLACK	2-core rubber cable	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

7 year extended warranty

Features & benefits

- 3W at 700mA
- Coastal protected
- IP68 ideal for outdoor areas and under water lighting
- Complete with wall fixings
- Robust cable for use outdoors
- Tilt & rotate for adjusting light
- Long lifetime of 70,000hrs

Light source
energy efficiency:



Beam angle: 26°

