



UL030RGBW

Colour change LED light (12W max.)

Features

IP rating	IP67
CSP Switchable	RGBW
Tilttable	360°
Rotation Angle	360°
LED Lifetime	50,000h L50
CRI	80 Ra

Installation information

UK Bathroom Zone	1
Construction Material	Stainless steel (316)
Weight	900g
Maximum Ambient Temperature	35°C
Electric Class (1, 2, 3)	3

Photometrics @ 25°C

Product code	W	Colour	Beam	lm	lm/W	lx @ 1m
UL030RGBW	3W	White (4000K)	45°	177	59	154
UL030RGBW	3W	Red	45°	106	53	60
UL030RGBW	3W	Green	45°	185	62	168
UL030RGBW	3W	Blue	45°	43	14	1

Wiring information

Cable / Flying Lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of Wiring Required	Series

LED driver

PR3011	N/A	Yes	Yes	1	1	2
--------	-----	-----	-----	---	---	---

Accessories

JB7	5-pole IP68 inline connector	Sold Separately
CR575RGBW	5-core PVC cable	Sold Separately
RC2819 / WC2820(BLK/W H) / TR2818	4/6/8 zone RF control for RGB & RGBW system	Sold Separately



collingwood

01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

5 year extended warranty

Features & benefits

- RGBW
- Coastal protected
- IP68 ideal for outdoor areas and under water lighting
- Complete with wall fixings for easy installation
- Can rotate and be angled to direct light
- Separate white LED for permanent use
- Compatible with a large range of controllers
- Marine grade stainless steel for use in outdoor and indoor environments

Beam angle: 45°

