



LEDLINE MAINS 400 45°

45° straight to mains wall washing light bar

Features

IK rating	IK02
IP rating	IP65
CSP Switchable	Fixed colour
Tilttable	180°
LED Lifetime	70,000h L70
CRI	80 Ra
SDCM	3 SDCM

Installation information

UK Bathroom Zone	2
Inrush Current	2.1A 0.1ms
Construction Material	Anodised aluminium
Weight	1.4kg
Maximum Ambient Temperature	35°C
SELV	Yes
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
ULM347M30	Black	19W	3000K	45°	1000	53	2320

Wiring information

Cable / Flying Lead	3m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of Wiring Required	Parallel

LED driver

N/A (integrated SELV driver)	220-240V	N/A	No	2	N/A	N/A
------------------------------	----------	-----	----	---	-----	-----

Accessories

ULBRACKET	2-piece black anodised aluminium bracket	Sold Separately
-----------	--	-----------------



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

7 year extended warranty

Features & benefits

19W

Coastal protected

IP65 ideal for outdoor environments

45° beam angle ideal for mid-level wall wash

Mains driver built-in for quick installation

Robust cable for permanent use outdoors

Light source
energy efficiency:



Beam angle: 45°

