



WL075

Silver straight to mains, high output LED wall light

Features

IP rating	IP65
CSP Switchable	Fixed colour
Dimmable Option	No
LED Lifetime	70,000h L70
CRI	80 Ra
SDCM	3 SDCM

Installation information

Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium
Weight	1.2kg
Maximum Ambient Temperature	40°C
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
WL075SNBM27	Silver	5.7W	2700K	12°	515	90	2763
WL075SNBM30	Silver	5.7W	3000K	12°	520	91	2789
WL075SNBM40	Silver	5.7W	4000K	12°	530	93	2843
WL075BNBM27	Black	5.7W	2700K	12°	515	90	2763
WL075BNBM30	Black	5.7W	3000K	12°	520	91	2789
WL075BNBM40	Black	5.7W	4000K	12°	530	93	2843
WL075ZNBM27	Bronze	5.7W	2700K	12°	515	90	2763
WL075ZNBM30	Bronze	5.7W	3000K	12°	520	91	2789

LED driver

N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A
------------------------------	----------	-----	----	-----	-----	-----

Accessories

No accessories required



01604 495 151
collingwoodlighting.com

- collingwoodled
- /collingwoodlighting
- collingwoodlighting

Guarantee

7 year extended guarantee available

Features & benefits

- 5.7W
- Coastal protected
- IP65 ideal for outdoor environments
- Single LED and lens combination for maximum efficiency and optimal light distribution.
- Straight to mains wall light, perfect for framing entrances and illuminating columns
- Anodised Aluminium is sleek and durable
- Long lifetime of 70,000hrs
- 7 year warranty

Light source
energy efficiency:



Beam angle: 12°

