**Step lights** specification sheet



# WL340

Asymmetric, straight to mains, brush finish step light

## Features

| | |
|---|---|
| **IP rating** | IP65 |
| **CSP Switchable** | Fixed colour |
| **Walk Over / Drive Over** | Walk over |
| **LED Lifetime** | 70,000h L70 |
| **CRI** | 80 Ra |
| **SDCM** | 3 SDCM |

## Installation information

| | |
|---|---|
| **Cut Out Size** | Ø 80mm |
| **UK Bathroom Zone** | 2 |
| **Inrush Current** | 9A 0.8ms |
| **Construction Material** | Stainless steel (316) |
| **Weight** | 1000g |
| **Maximum Ambient Temperature** | 35°C |
| **SELV** | Yes |
| **Electric Class (1, 2, 3)** | 1 |

## Photometrics @ 25°C

| Product code | W | Colour | Beam | lm | llm/W | lx @ 1m |
|---|---|---|---|---|---|---|
| WL340NW | 2.6W | 4000K | 50° | 59 | 22 | 65 |
| WL340WW | 2.6W | 3000K | 50° | 50 | 19 | 54 |
| WL340AB27 | 2.6W | 2700K | 50° | 49 | 19 | 52 |
| WL340ABWW | 2.6W | 3000K | 50° | 50 | 19 | 54 |

## Wiring information

| | |
|---|---|
| **Cable / Flying Lead** | 1m (H05RN-F) rubberised cable (outside diameter: 7mm) |
| **Type of Wiring Required** | Parallel |

## LED driver

| | | | | | | |
|---|---|---|---|---|---|---|
| N/A (integrated SELV driver) | 220-240V | N/A | No | 2 | N/A | N/A |

## Accessories

| | | |
|---|---|---|
| **Installation tube included** | | |
| **JB5** | Gel filled waterproof connector | Sold Separately |
| **WC 5-9** | Quick release waterproof joint | Sold Separately |

collingwood


**01604 495 151**
**collingwoodlighting.com**

collingwoodled

/collingwoodlighting

collingwoodlighting


## Guarantee

7 year extended warranty

## Features & benefits

2.6W

Coastal protected

Main voltage step light

Recessed, asymmetric wall or ground light perfect for illuminating walls, steps and pathways

Available in rustic cast stainless steel and sleek brushed stainless steel finishes

Installation tube included

**Beam angles:** 50° C0/C180 50° C90/C270

**Ø98mm**

